



CLAMP TYPE LINE TERMINAL SUITABLE FOR USE WITH COPPER OR ALUMINUM CONDUCTOR .25 TO .81 DIA

- NOTES:
- 1 ARRESTER PACKED FOR DOMESTIC SHIPMENT
 - 2 NET WEIGHT - 107 LB
 - 3 MAXIMUM CONTINUOUS LINE-TO-GROUND OPERATING VOLTAGE 36.5 KV RMS
 - 4 ANSI-70 GREY GLAZE
 - 5 ALTITUDE TO 12,000 FT
 - 6 DIMENSIONS SUBJECT TO ±3% TOLERANCE
 - 7 DUTY CYCLE VOLTAGE RATING 45 KV RMS

5/4 SEC 10KA IR KV	500 A SWITCHING SURGE IR KV	MAXIMUM 8/20 DISCHARGE VOLTAGE - KV AT					
		15 KA	30 KA	5 KA	10 KA	20 KA	40 KA
128	88.3	96.8	102	106	113	127	146

PART PORCELAIN STATION ARR		SCALE 1:2=1	
NAME 9L11ZGA045S			
DESIGN ALL	DATE 02/23/98	DWG NO S015334-00	REV. NO 00
DRAWN JVR	DATE 02/23/98		