

Capacitor Unit Details

Capacitor Part Number:

18L0062WH

Rated Voltage	4160 V	60 Hz
KVAR at Rated Voltage	9.8 kVAR	
Rated Capacitance	1.5 μ F	
Manufacturing tolerance for capacitor unit kvar	-0% to +15%	
Capacitor Unit BIL	95/95 kV	
Bushing Leakage Distance (Nominal)	12 in	305 mm
Number of Film Layers per Pad	2	
Total Film Pad Thickness	1.10 mil	
Dry Space Factor	24.6 %	
Number of Series Sections	4	
Number of Parallel Packs per Section	3	
Section Voltage	1040 Volts	
Volts/mil stress (film only)	945 Volts/mil	
Volts/mil stress (film and fluid)	758 Volts/mil	
Discharge Resistor Rating	17 M Ω	
Weight	36 Lbs	16.4 kg
Gallons of Dielectric Fluid	.71 Gal	
Ground Test	0 V	DC 0 sec
Dielectric Test	26000 V	DC 10 sec
Manufactured with Folded edges (Y/N)	No	

Additional Comments:

- Case thickness: Sides: 0.042", Cover: 0.05", Bottom: 0.09".
- Average losses of a stabilized unit in service is 0.1 W/kvar.
- Paint is an epoxy primer w/ urethane top coat meeting ANSI C57.12.31-2010 Pole Mounted Equipment .
- Internal elements will be extended foil and connected using ultrasonic welding.
- Capacitor unit operating temperature range is -50 to +50 deg. C.
- Maximum Bushing Torque 25 Ft-Lbs or 34 N-m.
- Percent Alteration on Surface Altered Film is 10% (avg.).
- Fluid Type (Non PCB) is DIELEKTROL VIIa, with a Dielectric Constant of 2.62.

