

Capacitor Unit Details

Capacitor Part Number:	<u>58L127WC60</u>		
Rated Voltage	7620 V	60 Hz	
KVAR at Rated Voltage	200 kVAR		
Rated Capacitance	9.14 μ F		
Manufacturing tolerance for capacitor unit kvar	-0% to	+10%	
Capacitor Unit BIL	95 kV		
Bushing Leakage Distance (Nominal)	12 in	305 mm	
Number of Film Layers per Pad	2		
Total Film Pad Thickness	1.00 mil		
Dry Space Factor	32.5 %		
Number of Series Sections	4		
Number of Parallel Packs per Section	2		
Section Voltage	1905 Volts		
Volts/mil stress (film only)	1905 Volts/mil		
Volts/mil stress (film and fluid)	1438 Volts/mil		
Discharge Resistor Rating	5.24 M Ω		
Weight	47.5 Lbs	21.6 kg	
Gallons of Dielectric Fluid	1.87 Gal		
Ground Test	0 V	AC	10 sec
Dielectric Test	15240 V	AC	10 sec
Manufactured with Folded edges (Y/N)	Yes		

Additional Comments:

- Case thickness: Sides: 0.042", Cover: 0.05", Bottom: 0.09".
- Average losses of a stabilized unit in service is 0.1 W/kvar.
- Paint is an epoxy primer w/ urethane top coat meeting ANSI C57.12.31-2010 Pole Mounted Equipment .
- Internal elements will be extended foil and connected using ultrasonic welding.
- Capacitor unit operating temperature range is -50 to +50 deg. C.
- Maximum Bushing Torque 25 Ft-Lbs or 34 N-m.
- Percent Alteration on Surface Altered Film is 10% (avg.).
- Fluid Type (Non PCB) is DIELEKTROL VIIa, with a Dielectric Constant of 2.62.

